



Standart Boru Çapları Standart Pipe Dimeter	Ø mm	Açma Aralığı Decoupling Distance	inç	C x B x E			A x G x L1			Kutu Box Adet Piece	Kutu Box Kg. Kg.
21,3	20	20-23	1/2	8	30	12	2,5	30	60	100	14
26,7	25	25-28	3/4	8	30	12	2,5	30	73	100	14
33,4	31	32-35	1	8	30	12	2,5	30	77	75	14
42,2	38	40-45	1 1/4	8	30	12	2,5	30	835	50	14
48,3	45	48-52	1 1/2 "	8	30	12	2,5	30	91	50	14
60,3	55	58-62	2 "	8	30	12	2,5	30	103	50	16
70,0	70	70-80	2 1/2 "	10	30	12	3,0	30	125	25	09
88,9	79	86-91	3 "	10	30	12	3,0	30	153	25	10
114,3	106	100-115	4 "	10	30	12	3,0	40	163	25	11
141,0	132	138-142	5 "	12	40	16	4,0	40	202	10	11
168,3	164	163-167	6 "	12	40	16	4,0	40	243	10	11
219,1	214	216-222	8 "	12	40	16	4,0	40	288	10	13,5
		246-250	10 "	12	40	16	4,0	40	323	5	7,9

 **PIPE CLAMPS WITH HEAVY DUTY (WHIT NUT)**

- » Pipe clamps with heavy load as installed to wall, ceiling or floor that is used as the element of fixing the pipes.
- » Pipe clamps with heavy load used in fleshy (heavy) pipe installations.
- » Fixing of the pipe clamps with nut is made as used rod & steel dove I.
- » It ensures sound insulation till 15 Db to the vibration damping with the EPDM insulation rubber.
- » It is covered with 15-20 sine against oxidation that is durable with special rubber according to DIN 53509 conditions. (Towards water, glycol, acid and bases.)

 **ХОМУТ УСИЙ (ГАЕЧНЫЙЛЕНН)**

- » Хомуты рассчитанные на тяжелые нагрузки, используются для монтажа труб, несущих большие нагрузки.

Pipe Clamps

All dimensions in charts and on drawings are in inches. Dimensions shown in parentheses are in millimeters unless otherwise specified.